



## ThinFlex Corporation

No. 8, Luke 2nd.Rd., Luzhu Dist., Kaohsiung City, 821, Taiwan, R.O.C.  
(Kaohsiung Science Park) Tel: +886-7-6955236 Fax: +886-7-6955539



### SAFETY DATA SHEET

THINFLEX- A

SDS DATE: 2018/01/18

---

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

---

### Product Name

ThinFlex-A

### Manufacturer's Name & Address

ThinFlex Corporation  
No. 8, Luke 2nd.Rd., Luzhu Dist.,  
Kaohsiung City, 821, Taiwan, R.O.C.

### Emergency Telephone Number

Tel: +886-7-6955236  
Fax: +886-7-6955539

---

## SECTION 2: HAZARDS IDENTIFICATION

---

### GHS Classification:

Not a dangerous substance or mixture. (Not classified).

### Potential Health Effects

Eyes: Not a probable route of exposure for film.

Skin: No irritation is expected from handling film.

Ingestion: Not a probable route of exposure for film.

Inhalation: Not a probable route of exposure for product as shipped.

---

## SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

---

Material	Product Component	CAS No.	Percentage (%)
Polyimide Film	Dielectric Layer	-----	5.61~18.76
Copper Foil	Conductive Layer	7440-50-8	94.39~81.24

---

## SECTION 4: FIRST AID MEASURES

---

Eye Contact: Flush eyes with water. Consult a physician if irritation persists.

Skin Contact: Wash with soap and water after handling. If skin irritation develops, consult a physician.

Ingestion: Not a probable route of exposure for films.

Inhalation: No specific intervention is indicated as the compound is not likely to be hazardous by inhalation.



ThinFlex

## ThinFlex Corporation

No. 8, Luke 2nd.Rd., Luzhu Dist., Kaohsiung City, 821, Taiwan, R.O.C.  
(Kaohsiung Science Park) Tel: +886-7-6955236 Fax: +886-7-6955539



---

### SECTION 5: FIRE-FIGHTING MEASURES

---

#### Flammable Properties

Not a fire or explosion hazard. The flammability characteristic of polyimide film is reported as "self-extinguishing". Polyimide film chars but does not burn. However, polyimide film will burn in an atmosphere of 100% oxygen. The major off-gases are carbon dioxide and carbon monoxide.

The processing of polyimide films can cause the generation of static charge. Precautions for static charges should also be taken when removing plastic films used as protective packaging for polyimide films.

#### Extinguishing Media

Use any available extinguishing media.

#### Fire Fighting Instructions

None required.

---

### SECTION 6: ACCIDENTAL RELEASE MEASURES

---

#### Safeguards (Personnel)

Use appropriate personal protective equipment during clean-up.

#### Accidental Release Measures

Practice good housekeeping to prevent and eliminate slipping hazards.

---

### SECTION 7: HANDLING AND STORAGE

---

#### Handling (Personnel)

Wash hands thoroughly after handling.

#### Storage

Store in a dry and cool place away from sunlight. Recommended storage conditions of below 25°C and below 70% humidity.

---

### SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

---

#### Engineering Controls



## ThinFlex Corporation

No. 8, Luke 2nd.Rd., Luzhu Dist., Kaohsiung City, 821, Taiwan, R.O.C.  
(Kaohsiung Science Park) Tel: +886-7-6955236 Fax: +886-7-6955539

### ThinFlex

Safe handling of polyimide films at high temperatures (above 200°C/ 392°F) requires adequate ventilation. If small quantities of polyimide film are involved, normal air circulation may be all that is needed in case of overheating. Whether or not existing ventilation is adequate at higher temperatures will depend on the combined factors of film quantity, temperature and exposure time.

### Personal Protective Equipment

Safety glasses are recommended as good industrial practice.

Respirators are not needed for normal use.

Special protective clothing is not needed for normal use.

Gloves are recommended as good industrial practice.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

Appearance:	Roll
Color:	Metallic Copper
Odor:	Odorless
Solubility in Water:	Insoluble
Thermal Decomposition:	520°C

---

## SECTION 10: STABILITY AND REACTIVITY

---

### Chemical Stability

Stable at normal temperatures and storage conditions.

### Incompatibility (Materials to Avoid):

None reasonably foreseeable.

### Hazardous Decomposition or By-Products:

At temperatures above 400°C, the major off-gases of polyimide film are carbon monoxide and carbon dioxide. The quantity and composition of decomposition products will depend on the combined factors of film quantity, temperature and exposure time.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

Not classified as a toxic or hazardous material.



## ThinFlex Corporation

No. 8, Luke 2nd.Rd., Luzhu Dist., Kaohsiung City, 821, Taiwan, R.O.C.  
(Kaohsiung Science Park) Tel: +886-7-6955236 Fax: +886-7-6955539



---

### SECTION 12: ECOLOGICAL INFORMATION

---

#### Aquatic Toxicity

Film is insoluble in water.

---

### SECTION 13: DISPOSAL CONSIDERATIONS

---

#### Waste Disposal

Incinerate or landfill in accordance with local laws and ordinances. Copper portions can be recycled.

---

### SECTION 14: TRANSPORT INFORMATION

---

Road: Not a hazardous product.

Water / Air: Not a hazardous product.

---

### SECTION 15: REGULATORY INFORMATION

---

None, since the product is not classified as hazardous.

---

### SECTION 16: OTHER INFORMATION

---

#### Medical Use

CAUTION: Do not use in medical applications involving permanent implantation in the human body.

#### Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. This information is based upon technical data believed to be reliable, and is offered in good faith by the manufacturer. Users should perform additional tests to establish the suitability of any products for their intended applications. This Material Safety Data Sheet and the information herein are subject to revision as additional knowledge and experience is gained.